

KÖMMERLING 70 AD

Double seal system.





chamber technology is at the heart of the KÖMMERLING 70 AD window system. In

particular, the possibility of using modern triple glazing or special functional glazing

up to 44 mm thick significantly improves the thermal insulation and sound insulation

technology either. An extensive ancillaries programme makes replacing old windows

with new ones utterly hassle-free.

values. KÖMMERLING 70 AD leaves nothing to be desired when it comes to fastening

THE BENEFITS AT A GLANCE:

KÖMMERLING 70 AD

- Classic offset window design with narrow profile sight lines.
- Increased thermal insulation with a U_f value of up to 1.2 W/(m²K).
- Wide range of glazing variants up to 44 mm thick for the use of triple glazing or special functional glazing.
- Improved quality of life thanks to perfect noise protection.
- Of lasting value thanks to its robust top quality.
- Outstanding handling ease and reliable functionality thanks to the most advanced technology.
- Available in white, in a laminated woodgrain design, plain colours and metallic colours.

KÖMMERLING 70 AD

Residential door system.

- Four-chamber design with steel reinforcement of maximum dimensions and welded corner connector for improved static properties.
- High level of tightness thanks to double sealing for thresholds with thermal break.
- Threshold connector for an accurate fit and sealing between the frame and threshold.
- Use of special functional glazing or residential door panelling up to 44 mm.
- Excellent burglary protection depending on the hardware equipment.
- Designs in woodgrain, plain colours and metallic colours.
- Maximum leaf sizes:
 Single-leaf residential door
 1100 x 2350 mm
 Double-leaf residential door
 1000 x 2350 mm (per leaf)



KÖMMERLING 70 RESIDENTIAL DOORS

COMPATIBLE AND COST-EFFECTIVE.

Residential doors in particular, and not just windows, give each home its own individual character.

Design your burglar-proof residential door according to your personal preferences with the KÖMMERLING 70 double seal system – with an inward or outward opening variant. Choose your favourite design from among a large number of door panelling options.

The residential door has been developed on the basis of a threshold concept that is already established at KÖMMERLING. The design features guarantee outstanding static properties in addition to optimal thermal insulation and sound insulation factors.



profine GmbHKÖMMERLING KUNSTSTOFFE

Postfach 2165 · 66929 Pirmasens · Germany Tel.: +49 (0) 6331 56 0 · Fax: +49 (0) 6331 56 2475 E-mail: info@koemmerling.de Internet: www.koemmerling.de

